

## 13-FL13

## Perm/Peel Film Tape

Product Description	13-FL13 has a clever differential adhesive system. One side has a high tack permanent adhesive and the other side has a medium tack removable adhesive.
Product Features	Perm/Peel adhesive system Clean removal after use Conforms to FDA Regulation 175.105 for indirect food contact. Resistant to UV, plasticizers and high temperature
Carrier	Polyester
Density	N/A
Adhesive Type	Perm/Peel
Total Thickness	0.05mm
Adhesive Tape Colour	Clear
Release Liner	White Glassine Paper gsm
Peel Adhesion	High/Low
Shear Strength	Medium High/Low
Elongation	N/A
Continuous Temp. Range	-25°C to +120°C
Minimum Application Temp.	+20°C
Available Widths	3mm – 1500mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Promotional posters, temporary holding of materials, flexible removable labels in food industry. Used to hold promotional items, CD's and card into literature and magazines.

**Tecman Speciality Materials** **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB  
**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.