

## 13-FL08

## Film Tape

Product Description	A double sided PET film tape with ultra clear bonding adhesive. Comes with twin PET release liners to add clarity and stability.
Product Features	Good initial bond strength Crystal clear adhesive Suitable for outdoor use Twin PET release liners
Carrier	PET Film
Density	N/A
Adhesive Type	Modified Polyacrylate
Total Thickness	0.70mm
Adhesive Tape Colour	Crystal Clear
Release Liner	Twin 30mic PET siliconised film
Peel Adhesion (N/25mm)	Medium High
Shear Strength	High
Elongation	>20%
Continuous Temp. Range	-40°C to +150°C
Minimum Application Temp.	+15°C
Available Widths	12mm – 1550mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Mounting graphics. Bonding fascia/screens with clear windows, camera lens protection, Laminating/mounting ITO films and other speciality window films.

**Tecman Speciality Materials** **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB  
**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.