

## 3M-4910VHB

## 3M 4910 VHB®

### Product Description

3M-4910 is a glass clear foamed acrylic tape with very high bond strength to most high surface energy surfaces.

### Product Features

Glass clear  
Available from 0.25mm to 2mm thickness  
Excellent bond to acrylics  
Suitable for outdoor use  
UL listing 746C

### Carrier

Foamed Acrylic

### Density

960 Kgm<sup>3</sup>

### Adhesive Type

Acrylic Foam

### Total Thickness

1.00mm

### Adhesive Tape Colour

Glass Clear

### Release Liner

Red Film 0.125mm

### Peel Adhesion

Very High

### Shear Strength

Very High

### Elongation

300%

### Continuous Temp. Range

-30°C to +93°C

### Minimum Application Temp.

+15°C

### Available Widths

3.00mm – 1220mm

### Available Formats

Sheets, Die Cutting, Pads, Rolls

### Common uses (not limited too)

Sign channel, glass, rigid plastics, foamed PVC, aluminium composite, acrylic fabrication, metal fabrication, trim attachment, light box fabrication, badge mount, GRP fabrication, sign fabrication

**Tecman Speciality Materials** **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB

**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.