

## 15-Vhpb09

## Vhpb - 1.14mm White

### Product Description

15-Vhpb09 is a white foamed acrylic tape with very high bond strength to most surfaces. Its specially formulated adhesive makes it one of the most useful Vhpb tapes.

Product Features	High adhesion to a wide variety of substrates Good resistance to solvents and moisture Excellent ageing, UV weathering properties Resistance to abrasion, corrosion and moisture Suitable for indoor and outdoor environments
Carrier	Foamed Acrylic
Density	760 kg/m <sup>3</sup>
Adhesive Type	Vhpb Acrylic
Total Thickness	0.64mm – 2.04mm
Adhesive Tape Colour	White
Release Liner	Printed Glassine Paper 120gsm
Peel Adhesion	Very High
Shear Strength	Very High
Elongation	300%
Continuous Temp. Range	-40°C to +80°C
Minimum Application Temp.	+15°C
Available Widths	3mm – 500mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Signage manufacturing, Georgian Bars, Sign channel, Automotive trim and badge attachment, metal and plastic fabrication.

**Tecman Speciality Materials** **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB  
**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.