

15-Vhpb12

Thermally Conductive **Vhpb** Tape

Product Description

15-Vhpb12 is a thermally conductive acrylic foam tape. Part of our Very High Performance Bond range, its thermally conductive properties are designed to offer superior transfer of heat from component to heat sinks. Its Vhpb bond strength makes it the preferred choice for bonding and mounting components and LED light strips to heat-sinks.

Product Features	Vhpb adhesive properties provide excellent strength for components Suitable for outdoor use Conformable foamed acrylic carrier for improved surface contact	
Carrier	Foamed Acrylic Transfer	
Carrier loading	Thermally conductive filler	
Density	1500 kgm ³	
Adhesive Type	Very High Performance Bond (Vhpb)	
Total Thickness	0.25mm	
Adhesive Tape Colour	White	
Release Liner	Red PE	
Surface Resistance (ASTM D-257)	5.0 Ω/cm (12.7 Ω/In) (x10 ⁻)	
Volume Resistivity (ASTM D-257)	2.0 Ω/cm (5.08 Ω/In) (x10 ⁻)	
Dialectric Breakdown Voltage (TEC-60243-1)	3.75 kV	
Dialectric Strength (TEC-60243-1)	15 kV/mm (381 volts/In)	
Thermal Conductivity (TCi)	0.6 W/(m/K) (0.347 Btu/(ft/hr/°F)	
Peel Adhesion (180°)	1200 g/cm ²	ASTM D-3330
Tensile Strength	9000 g/cm ²	ASTM D-897
Dynamic Shear (20min)	>5000 hours	ASTM D-1002
Dynamic Shear (72 hours)	>8000 hours	ASTM D-1002
Elongation	300%	
Continuous Temp. Range	-30°C to +100°C	
Minimum Application Temp.	+15°C	
Available Widths	3mm – 400mm	
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes	
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight	
Common uses (not limited too)	Bonding heat generating components to heat sinks or other cooling devices. Mounting LED light strips and units. Replacement of thermal grease and mechanical fixtures. For use within chip on board assemblies, LED/PDP Modules, LED Signage, backlit TV units and components within desktop, laptop and other hand held devices	

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB

T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.