

## 13-FL04

## Film Tape

Product Description	A double sided, self adhesive tape consisting of a transparent polyester film with a high tack modified acrylic adhesive and a red filmic release liner.
Product Features	Excellent initial bond strength Very good resistance to chemicals, UV and plasticisers Suitable for outdoor use Red filmic release liner.
Carrier	PET Film
Density	N/A
Adhesive Type	Modified Acrylic
Total Thickness	0.205mm
Adhesive Tape Colour	Clear
Release Liner	Red PP Film
Peel Adhesion (N/25mm)	Very High
Shear Strength	Very High
Elongation	200%
Continuous Temp. Range	-20°C to +90°C
Minimum Application Temp.	+20°C
Available Widths	3mm – 1000mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Mounting of moulded plastic parts, LCD screens, rubber/EPDM profiles, fabrics, roller blind assembly, lampshade manufacture, decorative profiles & mouldings in the furniture and automotive industries.

**Tecman Speciality Materials** **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB  
**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.