

13-FL06

Film Tape

Product Description

A white double sided self adhesive tape consisting of a conformable PVC film carrier with a heavy coating of modified acrylic adhesive. Excellent bond on critical materials such as PP, PE & rough surfaces.

Product Features

Excellent combination of high initial tack & long-term adhesion
Good temperature & UV resistance,
Suitable for outdoor use
Excellent chemical resistance

Carrier	PVC
Density	N/A
Adhesive Type	Modified Acrylic
Total Thickness	0.23mm
Adhesive Tape Colour	White
Release Liner	Amber Glassine Paper 65gsm
Peel Adhesion (N/25mm)	Very High
Shear Strength	High
Elongation	200%
Continuous Temp. Range	-35°C to +70°C
Minimum Application Temp.	+15 °C
Available Widths	3mm – 1250mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Banner hems, mounting rigid plastics, most metals, wood, rubber & foam, heavy decorative materials & displays, signs & scales. Excellent "general purpose" bond tapes.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.