

14-FM03

Foam Tape

| | |
|-------------------------------|--|
| Product Description | 14-FM03 is a low density PE foam tape with an aggressive modified acrylic adhesive. Conforms to BS7116 Glazing |
| Product Features | Aggressive modified acrylic adhesive Available in black or white Available from 2mm to 25mm thickness Suitable for external use |
| Carrier | PE Foam |
| Density | 33 Kg/m ³ |
| Adhesive Type | Modified Acrylic |
| Total Thickness | 2mm – 5mm |
| Adhesive Tape Colour | Black or White |
| Release Liner | Amber Glassine Paper 65gsm |
| Peel Adhesion (N/25mm) | High – Foam Destruction |
| Shear Strength | Medium |
| Elongation | 130% |
| Continuous Temp. Range | -18°C to +80°C |
| Minimum Application Temp. | + 15°C |
| Available Widths | 3mm – 1000mm |
| Available Formats | Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes |
| Shelf Life | 1 Year stored at 21°C, 50% RH and out of direct sunlight |
| Common uses (not limited too) | Mounting signage, decorative trim, rigid plastic mouldings, wooden mouldings, trim attachment, glazing bars. |

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.