

## 14-FM04

## High Grade Outdoor Foam Tape

Product Description	14-FM04 is a high density PE foam tape with high tack modified acrylic adhesive. This tape has been formulated into one of the best performing foam tapes available today.
Product Features	Very good initial bond Excellent bond to foamex, metal and composites High density PE foam Good shear strength Suitable for outdoor use.
Carrier	High Density PE Foam
Density	98 Kg/m <sup>3</sup>
Adhesive Type	Modified Acrylic
Total Thickness	0.8mm
Adhesive Tape Colour	White or Black
Release Liner	White Glassine Paper 90gsm
Peel Adhesion (N/25mm)	High – Foam Destruction
Shear Strength	Very high
Elongation	295%
Continuous Temp. Range	-35°C to +80°C
Minimum Application Temp.	+ 15°C
Available Widths	3mm – 1000mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Sign mounting and fabrication, kickboards, nameplates, glazing bars, decals, badges, Point of Sale, mirror mounting, trunking, decorative moulding, door frame trim and decorative rail.

**Tecman Speciality Materials** **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB  
**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.