

14-FM07

All Weather Foam Tape

Product Description	14-FM07 is a high grade PE foam tape with the latest generation of "All Weather" acrylic adhesive. This adhesive has been designed to be applied in temperatures as low as -12°C making it an essential product for exterior bonding.
Product Features	Very good initial bond Bonds at -12°C High density PE foam Good shear strength Suitable for outdoor use
Carrier	PE Foam
Density	76 Kg/m ³
Adhesive Type	All Weather Acrylic
Total Thickness	0.8mm
Adhesive Tape Colour	White
Release Liner	Blue PP Film
Peel Adhesion (N/25mm)	High – Foam Destruction
Shear Strength	Very high
Elongation	295%
Continuous Temp. Range	-35°C to +100°C
Minimum Application Temp.	- 12°C
Available Widths	3mm – 1600mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	External bonding in extreme conditions. Signage on Oil Rigs, Pipe marking, external aircraft components, Deep sea exploration, IP rated seals, Automotive components.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.