

Product Data Sheet

11-TR08

High Grade Outdoor Transfer Adhesive
- 0.125

Product Description	Heavy weight, clear transfer adhesive combining exceptional long term bonding performance with a high initial tack. This product is the perfect option for mounting high performance graphics.
Product Features	High coat-weight Exceptional temperature resistance Moisture stable liner for added stability Available in large format sheets UL969 for Marking and Labelling Systems. UL 746C UL CSA C22-2
Carrier	N/A
Density	N/A
Adhesive Type	Acrylic
Total Thickness	0.125mm
Adhesive Tape Colour	Clear
Release Liner	PC Printed Kraft Paper 120gsm
Peel Adhesion	High
Shear Strength	Very High
Elongation	N/A
Continuous Temp. Range	-30°C to +200°C
Minimum Application Temp.	10°C
Available Widths	3mm – 1000mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Nameplates, graphic overlays and membrane switch applications where a free film acrylic laminating adhesive is required. Applications that require long term 'holding power' and environmental resistance.

Tecman Speciality Materials A: Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB

T: 0800 328 35 32 E: customerservice@tecmanuk.com W: www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.