

0250570

PROTECTION FILM - AUTOMOTIVE SERIES

PRODUCT DESCRIPTION

Premium grade for freshly painted surfaces for long-term outdoor exposure. Applied after painting process, it provides reliable protection for painted surfaces susceptible to damage.

07

PRODUCT FEATURES

Good UV-resistance and perfect paint compatibility, 0250570 is the most reliable way to protect cars during the transportation process.

- Reliable protection
- Secure adhesion also at lower temperatures
- Secure adhesion during transport
- Cost savings as polishing or repair after demasking is eliminated
- Paint protection during outdoor storage up to 12 months
- Easy to apply and remove
- Easy disposal - film and the adhesive are environmentally friendly

06

BACKING MATERIAL

Polyolefinic Film

TOTAL THICKNESS

79 µm

ADHESIVE TYPE

EVA

ADHESION TO STEEL

0.8 N/cm

ADHESIVE TAPE COLOUR

Clear

ELONGATION AT BREAK

800%

TENSILE STRENGTH

30 N/cm

UV RESISTANCE

48 weeks

EASY TO REMOVE

Yes

SUITABLE FOR DIE-CUTTING

Yes

PAINT COMPATIBILITY

....

RESISTANCE TO CHEMICALS

....

MAIN APPLICATION (NOT LIMITED TOO)

Protection of painted surfaces during the assembly, storage and transportation process.
 Best protection solution for freshly painted car bodies.

04

03




02

EVALUATION KEY VERY GOOD ... GOOD .. MEDIUM • LOW

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

01



Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com