

0250575

## Protection Film - Automotive Series

**Product Description**

Economy grade for freshly painted surfaces for long-term outdoor exposure.

**Product Features**

Best protection solution for freshly painted car bodies. Applied after the painting process, the film provides reliable protection for painted surfaces susceptible to damage.

Due to the good UV-resistance and perfect paint compatibility, it's the most reliable way to protect cars during the transportation process.

- Reliable protection
- Secure adhesion during transport
- Cost savings as polishing or repair after demasking is eliminated
- Paint protection during outdoor storage up to 12 months
- Easy to apply and remove
- Easy disposal - both the film and the adhesive system are environmentally friendly

Backing Material	Polyolefinic Film
Total Thickness	59 µm
Adhesive Type	EVA
Adhesion to Steel	0.6 N/cm
Adhesive Tape Colour	White
Elongation at Break	650 %
Tensile Strength	24 N/cm
UV Resistance	52 weeks
Easy to Remove	Yes
Suitable for Die-cutting	Yes
Paint Compatibility	••••
Resistance to Chemicals	••••
Evaluation:	•••• very good ••• good •• medium • low

**Main Application (not limited too)**

Provides reliable protection for painted surfaces susceptible to damage.

**Tecman Speciality Materials** **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB  
**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.