

0250575

PRODUCT DESCRIPTION

PRODUCT FEATURES

PRODUCT DATA SHEET

PROTECTION FILM - AUTOMOTIVE SERIES

Economy grade for freshly painted surfaces for long-term outdoor exposure. Applied after the painting process, the film provides reliable protection for painted surfaces susceptible to damage.

Due to the good UV-resistance and perfect paint compatibility, it's the most reliable way to protect cars during the transportation process.

- Reliable protection
- · Secure adhesion during transport
- Cost savings as polishing or repair after demasking is eliminated
- Paint protection during outdoor storage up to 12 months
- · Easy to apply and remove
- Easy disposal both the film and the adhesive system are environmentally friendly

BACKING MATERIAL

TOTAL THICKNESS

ADHESIVE TYPE

ADHESION TO STEEL

ADHESIVE TAPE COLOUR

ELONGATION AT BREAK

TENSILE STRENGTH

UV RESISTANCE

EASY TO REMOVE

SUITABLE FOR DIE-CUTTING

PAINT COMPATIBILITY

RESISTANCE TO CHEMICALS

MAIN APPLICATION (NOT LIMITED TOO)

Polyolefinic Film

59 µm

EVA

0.6 N/cm

White

650%

24 N/cm

52 weeks

Yes

Yes

••••

••••

Provides reliable protection for painted surfaces susceptible to damage. Best protection solution for freshly painted car bodies.

EVALUATION KEY •••• VERY GOOD ••• GOOD •• MEDIUM • LOW

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



http://www.tecmanuk.com

