

0250577

PROTECTION FILM - AUTOMOTIVE SERIES

PRODUCT DESCRIPTION

High adhesion edge securing tape for freshly painted surfaces.

07

PRODUCT FEATURES

Ensures high strength adhesion and can be used to keep protection films securely in place, especially in areas of difficult geometries to prevent dust and humidity penetration.

Protection film consists of an UV-stabilised backing coated with a high adhesion EVA adhesive.

- Paint protection during outdoor storage up to 12 months
- Secure adhesion during transport
- Easy disposal - both the film and the adhesive system are environmentally friendly

06

BACKING MATERIAL

Polyolefinic Film

TOTAL THICKNESS

96 µm

ADHESIVE TYPE

EVA

ADHESION TO STEEL

3 N/cm

ADHESIVE TAPE COLOUR

White

ELONGATION AT BREAK

660%

TENSILE STRENGTH

21.5 N/cm

UV RESISTANCE

52 weeks

EASY TO REMOVE

Yes

SUITABLE FOR DIE-CUTTING

Yes

PAINT COMPATIBILITY

....

RESISTANCE TO CHEMICALS

....

MAIN APPLICATION (NOT LIMITED TOO)

Die-cutting and as printed marking, security or steering labels. Base material for heavy duty protection pads for bumpers and door edges.




04

03

02

EVALUATION KEY VERY GOOD ... GOOD .. MEDIUM • LOW

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

01

