

23-PR01

Low Tack Protection Film

Product Description

Low tack PE surface protection film

Product Features

Available in several colours
Low tack clean peel adhesive
Suitable for printed media (Subject to trial)

Carrier	PE
Density	N/A
Adhesive Type	Acrylic
Total Thickness	0.05mm
Adhesive Tape Colour	Clear/Blue/Green
Release Liner	N/A
Peel Adhesion (180° Peel)	Very Low
Shear Strength	N/A
Elongation	180 %
Continuous Temp. Range	+60°C
Minimum Application Temp.	+15°C
Available Widths	50mm – 1250mm
Available Formats	Rolls

Common uses (not limited too)

Protection of glass, printed media, uPVC, Screens, LCD displays
smooth plastic sheets, varnished surfaces, acrylic- and synthetic resin
varnish, high-grade steel, polished brass, polished

Tecman Speciality Materials Ltd **A:** Berrington House, Berrington Road, Leamington Spa, CV32 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.