

23-PR02

Medium Tack Protection Film

Product Description

Medium tack PE surface protection film

Product Features

Clean peel adhesive
Available in several colours
Medium tack level for short term protection
General purpose protection
Not suitable for printed graphics

Carrier	PE
Density	N/A
Adhesive Type	Acrylic
Total Thickness	0.05mm
Adhesive Tape Colour	Clear/Blue
Release Liner	N/A
Peel Adhesion (180° Peel)	Medium Low
Shear Strength	N/A
Elongation	200 %
Continuous Temp. Range	+50°C
Minimum Application Temp.	+15°C
Available Widths	50mm – 2500mm
Available Formats	Rolls

Common uses (not limited too)

Protection of uPVC extrusion, aluminium, glass and other non-printed media.

Tecman Speciality Materials Ltd **A:** Berrington House, Berrington Road, Leamington Spa, CV32 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.