

## 22-CR05

## Shot Blast Masking Tape

### Product Description

22-CR05 is a special shot blast masking tape. It uses a strong, thick and resistant paper backing which is designed to resist heavy shot. The product is also used as a protection material for grinding in workshops and base pads on tables during die-cutting in the shoe, leather and metal-working industry.

Product Features	0.7mm thickness give excellent durability High tack adhesive gives instant bond Clean removal with no adhesive residue Available in rolls or cut shapes
Skin	Flat paper
Thickness	0.6mm
Adhesive Type	Natural Rubber
Total Thickness	0.7
Adhesive Tape Colour	Cream
Release Liner	N/A - Self wound
Adhesion to Steel	Medium
Tensile Strength	180 N/cm
Elongation	6%
Continuous Temp. Range	-10°C to +60°C
Minimum Application Temp.	+15°C
Available Widths	Up to 915mm x 10m
Available Formats	Rolls and die-cut shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Masking for bead blast, sand blast and shot peening. Stone engraving, heavy metal stripping, rail bogie refurbishment, chassis repair and refurbishment, ship building, steel frame building stripping and finishing

**Tecman Speciality Materials** **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB UK  
**T:** +44 (0) 1926 337466 **E:** techsupport@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.