

## 22-CR01

## Masking Tape

### Product Description

General purpose masking tape, suitable for professional and consumer applications. Resistant to 40°C with good tack and removability after 24 – 48 hour masking.

Product Features	Resistant to 40°C Suitable as masking for brush, spray and roller applied paint processes Good tack and removability
Skin	Saturated crepe paper
Thickness	0.105mm
Backing thickness	78 gsm
Adhesive Type	Synthetic Rubber/Resins Clear Adhesive
Adhesive Tape Colour	Cream
Adhesion to Steel	> 3.5 N/cm
Tensile Strength	> 24 N/cm
Elongation	> 8%
Continuous Temp. Range	+40°C
Suitable for outdoor use	No
Available Widths	12mm x 50m 19mm x 50m 24mm x 50m 48mm x 50m Up to 1200mm
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	General purpose masking for building and decorating industries 24-48 hours masking applications such as internal fixtures, fittings, surfaces, sills and other internal areas

**Tecman Speciality Materials** **A:** Berrington House, Berrington Road, Leamington Spa, Warks, CV31 1NB

**T:** + 44 (0) 1926 337466

**E:** techsupport@tecmanuk.com

**W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.