

22-CR01

CREPE MASKING TAPE - 40°C

PRODUCT DESCRIPTION

General purpose masking tape, suitable for professional and consumer applications. Resistant to 40°C with good tack and removability after 24 – 48 hour masking.

PRODUCT FEATURES

Resistant to 40°C
 Suitable as masking for brush, spray and roller applied paint processes
 Good tack and removability

SKIN

Saturated crepe paper

THICKNESS

0.105mm

BACKING THICKNESS

78 gsm

ADHESIVE TYPE

Synthetic Rubber/Resins Clear Adhesive

ADHESIVE TAPE COLOUR

Cream

ELONGATION

> 8 %

ADHESION TO STEEL

> 3.5 N/cm

TENSILE STRENGTH

> 24 N/cm

CONTINUOUS TEMP. RANGE

40°C

SUITABLE FOR EXTERNAL USE

No

AVAILABLE WIDTHS

12mm, 19mm, 24mm, 48mm, up to 1200mm




SHELF LIFE

1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TOO)

General purpose masking for building and decorating industries 24 - 48 hours masking applications such as internal fixtures, fittings, surfaces, sills, and other internal areas.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

