

## 22-CR06

## Shot Blast Masking Tape - Ultra

### Product Description

22-CR06 is the highest performing shot blast masking tape. It uses a proprietary synthetic skin which is designed to resist the heaviest shot used today. The specialist adhesive is designed to provide excellent adhesion to almost every surface and yet remove cleanly leaving little or no adhesive residue after use.

### Product Features

250mic proprietary synthetic skin  
Resists blast up to 15 minutes at 8 bar  
Special reinforced adhesive gives instant bond and clean removal  
Suitable for bead blast, sand blast and shot peening  
Available in rolls or cut shapes

### Skin

Synthetic Fibre

### Thickness

0.25mm

### Adhesive Type

Toughened Rubber

### Total Thickness

0.55

### Adhesive Tape Colour

Cream

### Release Liner

White Glassine

### Adhesion to Steel

High

### Tensile Strength

285 N/cm

### Elongation

19%

### Continuous Temp. Range

-10°C to +80°C

### Minimum Application Temp.

+15°C

### Available Widths

Up to 915mm x 10m

### Available Formats

Rolls and die-cut shapes

### Shelf Life

1 Year stored at 21°C, 50% RH and out of direct sunlight

### Common uses (not limited too)

Masking for bead blast, sand blast and shot peening. Stone engraving, heavy metal stripping, rail bogie refurbishment, chassis repair and refurbishment, ship building, steel frame building stripping and finishing

**Tecman Speciality Materials** **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB UK

**T:** +44 (0) 1926 337466 **E:** techsupport@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.