

22-CR02

Masking Tape

Product Description	A premium grade crepe masking tape resistant to 80°C with instant adhesion and excellent removability after 7 – 10 day masking.
Product Features	Instant adhesive and excellent removability High grade crepe carrier that resists curling Resistant to 80°C Suitable for Automotive paint applications
Skin	Saturated crepe paper
Thickness	0.125mm
Adhesive Type	Natural Rubber/Resins
Total Thickness	125 µm
Adhesive Tape Colour	Yellow
Adhesion to Steel	> 2 N/cm
Tensile Strength	> 27 N/cm
Elongation	> 9%
Continuous Temp. Range	+80°C
Suitable for outdoor use	No
Available Widths	12mm x 50m 19mm x 50m 25mm x 50m 50mm x 50m Up to 1200mm
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Air drying and oven curing up to 80°C Automotive panel painting 7 – 10 day masking for hand paint, roller and spray applications

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks, CV31 1NB
T: + 44 (0) 1926 337466 **E:** techsupport@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.