

22-PT02

HIGH TEMPERATURE PET MASKING TAPE

PRODUCT DESCRIPTION

22-PT02 is a polyester tape coated on one side with a high temperature pressure sensitive silicone adhesive.

PRODUCT FEATURES

Available in several colours
 Clean removal adhesive
 Excellent chemical and solvent resistance
 Resistant to 220°C short term

CARRIER

Polyester

ADHESIVE TYPE

Silicone

TOTAL THICKNESS

0.065mm

ADHESIVE TAPE COLOUR

Blue, green and red

PEEL ADHESION

Medium

ELONGATION

10%+

CONTINUOUS TEMP. RANGE

+180°C

MINIMUM APPLICATION TEMP.

+21°C

AVAILABLE WIDTHS

3mm – 720mm




AVAILABLE FORMATS

Logs, rolls, sheets, discs, pads, and die-cut shapes

MAIN APPLICATIONS (NOT LIMITED TOO)

Electrical masking, powder coat masking, silicone wafer protection, chemical masking. Also used extensively for silicone splicing, core starting and other high temperature splice requirements.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

