

22-PT02

High Temperature PET Masking Tape

Product Description	22-PT02 is a polyester tape coated on one side with a high temperature pressure sensitive silicone adhesive.
Product Features	Available in several colours Clean removal adhesive Excellent chemical and solvent resistance Resistant to 220°C short term
Carrier	Polyester
Density	N/A
Adhesive Type	Silicone
Total Thickness	0.065mm
Adhesive Tape Colour	Blue, green and red
Release Liner	N/A
Peel Adhesion	Medium
Shear Strength	N/A
Elongation	10%+
Continuous Temp. Range	+180°C
Minimum Application Temp.	+21°C
Available Widths	3mm – 680mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Common uses (not limited too)	Electrical masking, powder coat masking, silicone wafer protection, chemical masking. Also used extensively for silicone splicing, core starting and other high temperature splice requirements.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks CV31 1NB, UK
T: +44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.