

12-TS04

Premium Outdoor Grade Tissue Tape

Product Description

A high coat-weight double sided tape with 12gsm tissue reinforcement carrier. The solvent acrylic adhesive has a very high initial tack along with good dynamic & static shear strength.

Product Features

High tack modified solvent acrylic adhesive
High temperature resistance
Moisture stable liner
Excellent UV & chemical resistance including most mineral oils, greases, fuels, aliphatic solvents, dilute acids and alkalis, and salts.
Suitable for outdoor use

Carrier	12gsm Tissue
Density	N/A
Adhesive Type	Modified solvent Acrylic
Total Thickness	0.115mm
Adhesive Tape Colour	Hazy
Release Liner	White MS Kraft Paper 120gsm
Peel Adhesion	High
Shear Strength	High
Elongation	2 %
Continuous Temp. Range	-20°C to +150°C
Minimum Application Temp.	+ 10°C
Available Widths	3mm – 1040mm
Available Formats	Rolls, Sheets, Die Cut Shapes and pads
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Nameplates, engraving laminates, membrane switch panels, directional signage including fire-route marking. Bonding foams and fabrics in high temperature applications including engine mount applications.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB
T: +44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.