

0250540v0

Protection Film - Automotive Series

Product Description

Protection film for painted and unpainted plastic components for long-term outdoor exposure.

Product Features

A premium grade self-adhesive film developed for the protection of delicate surfaces, such as painted bumpers.

- Cost saving due to reduction in rectification and final repair
- Preserves the paint finish, up to 6 months storage outdoor
- No special equipment needed, ensuring simple, low cost application and removal processes
- Good adhesion to the range of paint finishes, even during transportation (tested at speeds higher than 160 km/h – 100mph)
- Easy disposal. Both film and adhesive system are environmentally friendly

Backing Material	Polyolefinic Film
Total Thickness	75 µm
Adhesive Type	Synthetic Rubber
Adhesion to Steel	1.5 N/cm
Adhesive Tape Colour	White
Elongation at Break	450 %
Tensile Strength	16 N/cm
UV Resistance	24 weeks
Easy to Remove	Yes
Suitable for Die-cutting	Yes
Paint Compatibility	• • • •
Resistance to Chemicals	• • • •
Evaluation:	• • • • very good • • • good • • medium • low

Main Application (not limited too)

Protection against dirt and scratches during assembly, transport and storage of painted plastic parts or / and painted metal surfaces.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.