

11-TRR02

Transfer Adhesive Tape

Product Description

This toughened rubber reinforced bonding tape is excellent for bonding textured substrates. Its adhesive mass makes it suitable for bonding to textured surfaces.

Product Features

Good initial bond strength
Excellent bond to rubber and other LSE substrates
Toughened rubber adhesive gives excellent shear strength
Suitable for uneven and textured surfaces

Carrier	Scrim reinforcement
Density	N/A
Adhesive Type	Modified Rubber
Total Thickness	0.30mm
Adhesive Tape Colour	Hazy
Release Liner	White Glassine Paper 65gsm
Peel Adhesion	Very High
Shear Strength	High
Elongation	N/A
Continuous Temp. Range	-20°C to +60°C
Minimum Application Temp.	20°C
Available Widths	3mm - 1200mm
Available Formats	Rolls
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Bonding rubbers, textiles, leather and fabrics. Bonding machine labels to powdered coated surfaces. Estate agent boards.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmansm.co.uk **W:** www.tecmansm.co.uk

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.