

11-TR07

Outdoor Transfer Adhesive Tape

Product Description

Ultra-thin, clear transfer adhesive combines exceptional long term bonding performance with a high initial tack. This product is the perfect option for mounting high performance graphics.

Product Features

Very clear
Approved to UL969 for Marking and Labelling Systems.
Exceptional temperature resistance
Moisture stable liner for added stability
Available in large format sheets

Carrier	N/A
Density	N/A
Adhesive Type	Acrylic
Total Thickness	0.065mm
Adhesive Tape Colour	Clear
Release Liner	PC Printed Kraft Paper 120gsm
Peel Adhesion	High
Shear Strength	Very High
Elongation	N/A
Continuous Temp. Range	-30°C to +200°C
Minimum Application Temp.	10°C
Available Widths	3mm – 1000mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Nameplates, graphic overlays and membrane switch applications where a free film acrylic laminating adhesive is required. Applications that require long term 'holding power' and environmental resistance.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB

T: + 44 (0) 1926 337466

E: customerservice@tecmanuk.com

W: www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.