

11-TR11

Conductive Transfer Adhesive Tape

Product Description

A modified acrylic transfer adhesive loaded with electrically conductive particles. The product is electrically conductive through the Z axis.

Product Features

Very high bond strength
Conforms to UL723
Resistivity of 0.005 ohm. Volume resistivity of 0.5 ohms-cm
Suitable for outdoor use

Carrier	N/A
Density	N/A
Adhesive Type	Conductive Acrylic
Total Thickness	0.051mm
Adhesive Tape Colour	Hazy
Release Liner	White MS Kraft Paper 120gsm
Peel Adhesion	Medium High
Shear Strength	Medium High
Elongation	N/A
Continuous Temp. Range	-34°C to +107°C
Minimum Application Temp.	+15°C
Available Widths	3mm – 1250mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Anti-static components, conductive gaskets, Earth strips, replacing solder points.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.