

11-TR09

Transfer Adhesive Tape

Product Description

The original correx bonding tape for the “Estate Agent” boards. This product is also used in a wide variety of other applications due to its high initial bond and heavy coat-weight of adhesive

Product Features

Not suitable for extended outdoor use
Bonds well to LSE substrates
Used for manufacture of Estate Agent boards
Used for manufacture of leather goods

Carrier	N/A
Density	N/A
Adhesive Type	Hot-melt Rubber
Total Thickness	0.4mm
Adhesive Tape Colour	Hazy
Release Liner	White Glassine Paper 90gsm
Peel Adhesion	Very High
Shear Strength	Low
Elongation	300%
Continuous Temp. Range	-20°C to +55°C
Minimum Application Temp.	20°C
Available Widths	19mm, 25mm & 38mm
Available Formats	Rolls, Pads
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Estate agents board manufacture, leather goods, bonding textiles and fabrics during assembly. Bonding the most difficult substrates.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecman.co.uk **W:** www.tecman.co.uk

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.