

## 11-TR06

## Transfer Adhesive Tape

### Product Description

11-TR06 is a very aggressive synthetic rubber transfer adhesive. Its exceptional adhesion properties make it a fantastic alternative to spray, roller or brush applied adhesives.

### Product Features

Very high initial tack level  
Bonds well to LSE substrates  
Very high temperature performance for its class  
Not UV resistant

Carrier	N/A
Density	N/A
Adhesive Type	Synthetic Rubber
Total Thickness	0.060mm
Adhesive Tape Colour	Clear
Release Liner	Blue Green Super Calendared Glassine 90gsm
Peel Adhesion	Very High
Shear Strength	Medium High
Elongation	N/A
Continuous Temp. Range	-40°C to +110°C
Minimum Application Temp.	+10°C
Available Widths	25mm – 1000mm
Available Formats	Logs, Rolls, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

### Common uses (not limited too)

General purpose foam bonding such as gaskets, cushioning pads, sound deadening and insulation materials. Interior Automotive trim and business machine insulation.

**Tecman Speciality Materials** **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB  
**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.