

13-FL01

Film Tape

Product Description

13-FL01 has a polyester carrier coated with a high tack, modified, solvent free, acrylic adhesive. The tape has been specially formulated with an extra high coat-weight of adhesive on either side.

Product Features

Very high initial bond
Good UV and plasticisers resistance
Good low temperature bonding
Components conform to FDA175.102 for indirect food contact

Carrier	Polyester
Density	N/A
Adhesive Type	Modified Emulsion Acrylic
Total Thickness	0.19mm
Adhesive Tape Colour	Clear
Release Liner	White Glassine Paper 65gsm
Peel Adhesion (N/25mm)	High
Shear Strength	High
Elongation	50%
Continuous Temp. Range	-30°C to +100°C
Minimum Application Temp.	+ 15°C
Available Widths	3mm – 1550mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Used for demanding bonding applications where a high initial bond is required. Bonding to uneven surfaces. Panel, nameplate & foam lamination applications where bond to LSE substrates is critical.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB

T: + 44 (0) 1926 337466

E: customerservice@tecmanuk.com

W: www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.