

13-FL02

Film Tape

Product Description

13-FL02 has a uPVC carrier coated with an exceptionally high tack, high peel LSE acrylic adhesive. Performs well in many difficult bonding and splicing applications.

Product Features

Exceptionally high tack and peel strength
Meets compositional requirements of FDA Reg 21 CFR175.105
High coat-weight provides gap filling
Excellent UV, water and acid resistance

Carrier	UPVC Film
Density	N/A
Adhesive Type	Modified LSE Acrylic
Total Thickness	0.22mm
Adhesive Tape Colour	Hazy
Release Liner	White Glassine Paper 90gsm
Peel Adhesion (N/25mm)	Very high
Shear Strength	Medium
Elongation	70 %
Continuous Temp. Range	-50 to + 70°C
Minimum Application Temp.	+ 10°C
Available Widths	3mm – 1400mm
Available Formats	Sheets, Die Cutting, Pads, Rolls
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Bonding fabrics, rubbers and other LSE substrates. For use in the food industry for indirect food contact. Bonding decorative trim, automotive lining and splicing applications.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.