

13-FL12

Film Tape

Product Description

High performance synthetic rubber adhesive exhibits exceptional tack and peel strength. The high coat-weight on both sides enables it to key into textured surfaces.

Product Features

Very high initial tack
Excellent bond to LSE surfaces
Soft adhesive flows well into fibrous substrates
Excellent bond properties to low density foams
Excellent bond properties to porous substrates

Carrier	Polypropylene
Density	N/A
Adhesive Type	Synthetic Rubber
Total Thickness	0.14mm
Adhesive Tape Colour	Hazy
Release Liner	Blue/Green Supercalendered Glassine Paper 90gsm
Peel Adhesion	Very High
Shear Strength	Medium
Elongation	70 %
Continuous Temp. Range	-40°C to +55°C
Minimum Application Temp.	+15°C
Available Widths	3mm – 1000mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes

Common uses (not limited too)

Bonding thin plastic films, fabrics and other flexible substrates. Used extensively for sail-making and other seam reinforcement applications. The ultimate “sticks all” adhesive.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.