

14-FM01

Foam Tape

Product Description

14-FM01 is an economical, medium density PE foam coated with an aggressive hot-melt rubber adhesive. It exhibits very high initial tack.

Product Features

Very high initial tack level
Approved to BS7950:1997 for security glazing
Available in black or white and in thicknesses of 1mm – 25mm
Not recommended for outdoor use or under UV conditions

Carrier	PE Foam
Density	55 kgm ³
Adhesive Type	Hot-melt Rubber
Total Thickness	1mm – 25mm
Adhesive Tape Colour	White
Release Liner	Amber Glassine Paper 65gsm
Peel Adhesion (N/25mm)	High – Foam Destruction
Shear Strength	Medium
Elongation	250%
Continuous Temp. Range	-18°C to +60°C
Minimum Application Temp.	+ 15°C
Available Widths	3mm – 1000mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Bonding rigid plastic parts in white goods applications, bonding paper, card and board, Point of Sale and promotional goods. Security glazing applications.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.