

14-FM03

Foam Tape

Product Description

14-FM03 is a low density PE foam tape with an aggressive modified acrylic adhesive. Conforms to BS7116 Glazing

Product Features

Aggressive modified acrylic adhesive
Available in black or white
Available from 2mm to 25mm thickness
Suitable for external use

Carrier	PE Foam
Density	33 Kg/m ³
Adhesive Type	Modified Acrylic
Total Thickness	2mm – 5mm
Adhesive Tape Colour	Black or White
Release Liner	Amber Glassine Paper 65gsm
Peel Adhesion (N/25mm)	High – Foam Destruction
Shear Strength	Medium
Elongation	130%
Continuous Temp. Range	-18°C to +80°C
Minimum Application Temp.	+ 15°C
Available Widths	3mm – 1000mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Mounting signage, decorative trim, rigid plastic mouldings, wooden mouldings, trim attachment, glazing bars.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB

T: + 44 (0) 1926 337466

E: customerservice@tecmanuk.com

W: www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.