

15-Vhpb05

Vhpb - 2.0mm Clear

Product Description

15-**Vhpb05** is a glass clear foamed acrylic tape with very high bond strength to most high surface energy surfaces. Its solid construction and clear characteristics make it one of the most useful **Vhpb** tapes.

Product Features

Glass clear
Excellent bond to acrylics
Suitable for outdoor use
Bonds most metals and finishes

Carrier	Foamed Acrylic Vhpb Tape
Density	850 kgm ³
Adhesive Type	Vhpb Acrylic
Total Thickness	2.0 mm
Adhesive Tape Colour	Glass Clear
Release Liner	Red Siliconised Film 0.085mm
Peel Adhesion	Very High
Shear Strength	Very High
Elongation	300 % +
Continuous Temp. Range	-30°C to +100°C
Minimum Application Temp.	+15°C
Available Widths	3mm – 800mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Sign channel, glass, rigid plastics, foamed PVC, aluminium composite, acrylic fabrication, metal fabrication, trim attachment, light box fabrication, badge mount, GRP fabrication, sign fabrication

Tecman Speciality Materials A: Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.