

## 15-Vhpb07

## Vhpb Tape – 1.14mm Grey

### Product Description

15-Vhpb07 is a LOW APPLICATION TEMPERATURE Vhpb tape which provides a good combination of adhesion to LOW SURFACE ENERGY surfaces, conformability and initial tack. 15-Vhpb07 is specially formulated for application temperatures approaching freezing.

### Product Features

Application Temperature 0°C  
Resistant to moisture and plasticiser  
Resistant to Ultra violet {UV} light  
Resistant to abrasion, corrosion  
Suitable for indoor and outdoor environments  
Bonds LSE substrates

Carrier	Foamed Acrylic
Density	780 kgm <sup>3</sup>
Adhesive Type	Acrylic Foam
Total Thickness	1.14mm
Adhesive Tape Colour	Grey
Release Liner	Red Siliconised Film 0.085mm
Peel Adhesion	Very High
Shear Strength	Very High
Elongation	300 %
Continuous Temp. Range	-30°C to +80°C
Minimum Application Temp.	+0°C
Available Widths	0 – 450mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

### Common uses (not limited too)

Signage manufacturing, metals and composites, sign channel to aluminium and PVC, glazing bars, Automotive Trim attachment, Constructional bonding and exterior mounting.

**Tecman Speciality Materials Ltd** A: Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB

T: + 44 (0) 1926 337466 E: customerservice@tecmanuk.com W: www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.