

3M-9473

3M 9473 VHB®

Product Description

3M 9473 is a 0.25mm clear 3M™ VHB™ Transfer with very high shear holding power. Bond strength increases substantially with natural ageing.

Product Features

Excellent UV resistance
Adhesive will resist weather, solvents and water
Suitable for outdoor use
Thermal conductivity (0.0016 Watt/cm °C)
Exceptional heat resistance (Short term 260 °C)

Carrier	Foamed Acrylic Transfer
Density	N/A
Adhesive Type	VHB
Total Thickness	0.25mm
Adhesive Tape Colour	Clear
Release Liner	PC Printed Paper 100gsm
Peel Adhesion	High
Shear Strength	Very High
Elongation	300%
Continuous Temp. Range	-30°C to +150°C
Minimum Application Temp.	+15°C
Available Widths	3mm – 1550mm
Available Formats	Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Excellent for bonding decorative metal trim, and bonding flexible circuits to aluminium rigidizers or heat sinks.

Tecman Speciality Materials **A:** Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.