

## 00-5012

### Double Sided PET/Acrylic Adhesive Film Tape

#### Product Description

A double sided self adhesive tape consisting of a transparent polyester film with a very well balanced modified acrylic adhesive.

#### Product Features

Excellent balance of peel, shear and tensile strength  
Resistant to elevated temperatures (Up to 200°C)  
Very good resistance to chemicals, UV and plasticisers  
Approved to UL94 V0  
Red PP release liner.

#### Carrier

PET Film

#### Density

N/A

#### Adhesive Type

Modified Acrylic

#### Total Thickness

0.205mm

#### Adhesive Tape Colour

Glass Clear

#### Release Liner

Red PP Film

#### Peel Adhesion (N/25mm)

Very High

#### Shear Strength

Very High

#### Elongation

200%

#### Continuous Temp. Range

-20°C to +100°C

#### Minimum Application Temp.

+20°C

#### Available Widths

3mm – 1370mm

#### Available Formats

Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes

#### Shelf Life

1 Year stored at 21°C, 50% RH and out of direct sunlight

#### Common uses (not limited too)

Mounting of moulded plastic parts, rubber/EPDM profiles, fabrics, roller blind assembly, lampshade manufacture, decorative profiles & mouldings in the furniture and automotive industries, aerospace fit-out.

**Tecman Speciality Materials A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB

**T:** + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.