

15-Vhpb09

Vhpb - 1.14mm White

Product Description

15-**Vhpb09** is a white foamed acrylic tape with very high bond strength to most surfaces. Its specially formulated adhesive makes it one of the most useful **Vhpb** tapes.

Product Features

High adhesion to a wide variety of substrates
Good resistance to solvents and moisture
Excellent ageing, UV weathering properties
Resistance to abrasion, corrosion and moisture
Suitable for indoor and outdoor environments

| | |
|---------------------------|--|
| Carrier | Foamed Acrylic |
| Density | 760 kgm ³ |
| Adhesive Type | Vhpb Acrylic |
| Total Thickness | 0.64mm – 2.04mm |
| Adhesive Tape Colour | White |
| Release Liner | Printed Glassine Paper 120gsm |
| Peel Adhesion | Very High |
| Shear Strength | Very High |
| Elongation | 300% |
| Continuous Temp. Range | -40°C to +80°C |
| Minimum Application Temp. | +15°C |
| Available Widths | 3mm – 500mm |
| Available Formats | Logs, Rolls, Sheets, Discs, Pads, Die-cut Shapes |
| Shelf Life | 1 Year stored at 21°C, 50% RH and out of direct sunlight |

Common uses (not limited too)

Signage manufacturing, Georgian Bars, Sign channel, Automotive trim and badge attachment, metal and plastic fabrication.

Tecman Speciality Materials A: Berrington House, Berrinton Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.