

## 26-LM01

## Aluminium Foil Tape – Class 0

### Product Description

26-LM01 is a high performance aluminium foil tape with an excellent adhesive and a strong 35mic aluminium foil backing. The product is Class 0 rated and has a good quality glassine release liner.

### Product Features

Class 0 Rating  
Resists flame, weather, UV and moisture  
Thermally conductive for heating and cooling efficiency  
35 micron aluminium foil backing

Carrier	Aluminium Foil – Level 3
Density	N/A
Adhesive Type	Rubber
Total Thickness	0.07mm
Adhesive Tape Colour	Silver
Release Liner	White Glassine
Peel Adhesion	High
Shear Strength	High
Elongation	3%
Continuous Temp. Range	-10°C to +60°C
Minimum Application Temp.	+15°C
Available Widths	24mm, 48mm, 72mm, 96mm
Available Formats	Rolls
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

### Common uses (not limited too)

HVAC, Vibration and noise reduction in aircraft, thermal conducting and Grounding, bonding and EMI shielding

**Tecman Speciality Materials** A: Berrington House, Berrington Road, Leamington Spa, Warwickshire, CV31 1NB

T: + 44 (0) 1926 337466 E: [customerservice@tecmanuk.com](mailto:customerservice@tecmanuk.com) W: [www.tecmanuk.com](http://www.tecmanuk.com)

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.