

31-ST01

Hook & Loop Fastening System

Product Description

The traditional hook and loop fastening system has a very aggressive rubber adhesive making it suitable for almost any surface. The hook and loop fastening side is both durable and secure.

Product Features

High tack adhesive
Available in black or white
Available in width up to 100mm

Fastening Face	Hook and Loop
Density	N/A
Adhesive Type	Rubber
Total Thickness	Approx 1.5mm
Adhesive Tape Colour	Black or White
Release Liner	White Glassine Paper 120gsm
Peel Adhesion	High
Shear Strength	High
Elongation	N/A
Continuous Temp. Range	-15°C to +70°C
Minimum Application Temp.	+20°C
Available Widths	16mm, 20mm, 25mm, 30mm, 50mm & 100mm
Available Formats	Rolls & Pads
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight

Common uses (not limited too)

Exhibition and display units. Temporary holding of graphics.
Repositionable signs, door plaques and temporary markers.
Automotive and transportation interiors. Textiles and boat cover manufacture.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.