

## 11-TR06

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

### ADHESIVE TYPE

### TOTAL THICKNESS

### ADHESIVE TAPE COLOUR

### RELEASE LINER

### PEEL ADHESION

### SHEAR STRENGTH

### CONTINUOUS TEMP. RANGE

### MINIMUM APPLICATION TEMP.

### AVAILABLE WIDTHS

### AVAILABLE FORMATS

### SHELF LIFE

### MAIN APPLICATIONS (NOT LIMITED TOO)

# TECHNICAL DATA SHEET

## ULTRA-HIGH TACK TRANSFER ADHESIVE TAPE

11-TR06 is a very aggressive synthetic rubber transfer adhesive. Its exceptional adhesion properties make it a fantastic alternative to spray, roller or brush applied adhesives.

Very high initial tack level  
Bonds well to LSE substrates  
Very high temperature performance for its class  
Not UV resistant

Synthetic Rubber

0.060mm

Clear

Blue Green Super Calendared Glassine 90gsm

Very High

Medium High

-40°C to 110°C

10°C

25mm – 1000mm

Logs, rolls, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

General purpose foam bonding such as gaskets, cushioning pads, sound deadening and insulation materials. Interior Automotive trim and business machine insulation.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC120 | Issue 6 | Sept 2018

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01