

11-TR07

PRODUCT DESCRIPTION

PRODUCT FEATURES

TECHNICAL DATA SHEET

HIGH GRADE TRANSFER ADHESIVE TAPE

Ultra-thin, clear transfer adhesive combines exceptional long term bonding performance with a high initial tack. This product is the perfect option for mounting high performance graphics.

Very clear
Approved to UL969 for Marking and Labelling Systems.
Exceptional temperature resistance
Moisture stable liner for added stability
Available in large format sheets

ADHESIVE TYPE

Acrylic

TOTAL THICKNESS

0.065mm

ADHESIVE TAPE COLOUR

Clear

RELEASE LINER

PC Printed Kraft Paper 120gsm

PEEL ADHESION

High

SHEAR STRENGTH

Very High

CONTINUOUS TEMP. RANGE

-30°C to 200°C

MINIMUM APPLICATION TEMP.

10°C

AVAILABLE WIDTHS

3mm – 1000mm

AVAILABLE FORMATS

Logs, rolls, sheets, discs, pads, and die-cut shapes

SHELF LIFE

1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TOO)

Nameplates, graphic overlays and membrane switch applications where a free film acrylic laminating adhesive is required. Applications that require long term 'holding power' and environmental resistance.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC121 | Issue 6 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01