

**15-VHPB07**

**VHPB TAPE – 1.14MM GREY**

**PRODUCT DESCRIPTION**

A low application temp. Vhpb tape, provides a good combination of adhesion to LSE surfaces, conformability and initial tack. Specially formulated for application temperatures approaching freezing.

**PRODUCT FEATURES**

Application Temperature 0°C  
 Resistant to moisture and plasticiser  
 Resistant to Ultra violet {UV} light  
 Resistant to abrasion, corrosion  
 Suitable for indoor and outdoor environments  
 Bonds LSE substrates  
 Available in 3mm - 450mm widths  
 Available in logs, rolls, sheets, discs, pads, and die-cut shapes

**CARRIER**

Foamed Acrylic

**DENSITY**

780 kgm<sup>3</sup>

**ADHESIVE TYPE**

Acrylic Foam

**TOTAL THICKNESS**

1.14mm

**ADHESIVE TAPE COLOUR**

Grey

**RELEASE LINER**

Red Siliconised Film 0.085mm

**PEEL ADHESION**

Very High

**SHEAR STRENGTH**

Very High

**ELONGATION**

300%

**CONTINUOUS TEMP. RANGE**

-30°C to 80°C

**MINIMUM APPLICATION TEMP.**

0°C

**SHELF LIFE**




1 Year stored at 21°C, 50% RH and out of direct sunlight

**MAIN APPLICATIONS (NOT LIMITED TOO)**

Signage manufacturing, metals and composites, sign channel to aluminium and PVC, glazing bars, Automotive Trim attachment, Constructional bonding and exterior mounting.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

08  
07  
06  
05  
04  
03  
02  
01