

15-VHPB11

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

VHPB TAPE – 1.14MM GREY

15-Vhpb11 is part of our Signmakers Range of Vhpb tapes. These exceptional products offer true Vhpb performance at economical pricing.

Good initial bond
Resistant to moisture, plasticiser and Ultra violet (UV) light
Resistant to abrasion, corrosion
Bonds medium and high surface energy substrates
Alternative to 3M RP45
Available in 3mm - 800mm widths
Available in logs, rolls, sheets, discs, pads, and die-cut shapes

Foamed Acrylic

780 kgm³

Acrylic Foam

1.14mm

Grey

Red Siliconised Film 0.085mm

Very High

Very High

300%

-40°C to 100°C

0°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

Signage manufacturing, metals and composites, sign channel to aluminium and PVC, glazing bars. Constructional bonding and exterior mounting.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC139 | Issue 6 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01