

## 3M-9473

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

### CARRIER

### ADHESIVE TYPE

### TOTAL THICKNESS

### ADHESIVE TAPE COLOUR

### RELEASE LINER

### PEEL ADHESION

### SHEAR STRENGTH

### ELONGATION

### CONTINUOUS TEMP. RANGE

### MINIMUM APPLICATION TEMP.

### AVAILABLE FORMATS

### SHELF LIFE

### MAIN APPLICATIONS (NOT LIMITED TO)

# TECHNICAL DATA SHEET

## 3M 9473 VHB® TAPE

3M 9473 is a 0.25mm clear 3M™ VHB™ Transfer with very high shear holding power. Bond strength increases substantially with natural ageing.

Excellent UV resistance  
Adhesive will resist weather, solvents and water  
Suitable for outdoor use  
Thermal conductivity (0.0016 Watt/cm °C)  
Exceptional heat resistance (Short term 260 °C)  
Available in 3mm - 1550mm widths

Foamed Acrylic Transfer

VHB

0.25mm

Clear

PC Printed Paper 100gsm

High

Very High

300%

-30°C to 150°C

15°C

Logs, rolls, sheets, discs, pads, and die-cut shapes.

1 Year stored at 21°C, 50% RH and out of direct sunlight

Excellent for bonding decorative metal trim, and bonding flexible circuits to aluminium rigidizers or heat sinks.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC143 | Issue 6 | Sept 2018

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01