

22-CR05

PRODUCT DESCRIPTION

PRODUCT FEATURES

TECHNICAL DATA SHEET

SHOT BLAST MASKING TAPE

Has a strong, thick & resistant paper backing designed to resist heavy shot. Used as a protection material for grinding in workshops and base pads on tables during die-cutting in the shoe, leather and metal-working industry.

0.7mm thickness give excellent durability
High tack adhesive gives instant bond
Clean removal with no adhesive residue
Available in rolls or cut shapes

SKIN

Flat paper

THICKNESS

0.6mm

ADHESIVE TYPE

Natural Rubber

TOTAL THICKNESS

700 µm

ADHESIVE TAPE COLOUR

Cream

ELONGATION

6%

ADHESION TO STEEL

Medium

TENSILE STRENGTH

180 N/cm

CONTINUOUS TEMP. RANGE

-10°C to +60°C

MINIMUM APPLICATION TEMP.

15°C

AVAILABLE WIDTHS

up to 915mm x 10m

SHELF LIFE

1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TOO)

Masking for bead blast, sand blast and shot peening.
Stone engraving, heavy metal stripping, rail bogie refurbishment, chassis repair & refurbishment, ship building, steel frame building stripping & finishing.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

